

US009638424B2

(12) United States Patent

Towner

(10) Patent No.: US 9,638,424 B2 (45) Date of Patent: May 2, 2017

(54)	ELONGA	TED GRIPPING DEVICE	1,021,290 A			
(71)	Applicant:	Joseph Towner, Portland, MI (US)	1,284,323 A			
(72)	Inventor:	Joseph Towner, Portland, MI (US)	1,934,801 A			
(*)	Notice:	Subject to any disclaimer, the term of this	2,135,232 A			
		patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.	2,587,383 A			
		0.5.c. 12 1(0) by 0 days.	2,591,499 A			
(21)	Appl. No.:	: 14/560,249	3,171,386 A			
(22)	Filed:	Dec. 4, 2014	4,105,238 A			
(65)	Dulay Dublication Data	Duian Dublication Data	4,449,743 A			
(65)			4,478,449 A			
	US 2016/0	0010870 A1 Jan. 14, 2016	5,253,408 A			

Related U.S. Application Data

- (60) Provisional application No. 62/021,743, filed on Jul. 8, 2014.
- (51) Int. Cl. F24B 15/10 (2006.01) B25J 1/04 (2006.01)
- (52) **U.S. Cl.** CPC *F24B 15/10* (2013.01); *B25J 1/04* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

741,816 A *	10/1903	McKinniss	F24B 15/10
			294/104
776,591 A *	12/1904	Hower	F24B 15/10
			294/11

Althouse F24B 15/10	3/1912	*	21,290 A	1,02
294/1				
Hansen F24B 15/10	11/1918	*	84,323 A	1,28
294/1				
Hiner A01K 15/003	11/1933	*	34,801 A	1,93
119/800				
Dawn A63B 47/02	11/1938	*	35,232 A	2,13
294/1				
Reents A01K 15/003	2/1952	*	87,383 A	2,58
119/806				
Bible B25B 9/00	4/1952	*	91,499 A	2,59
294/1				
De Ronde A01K 15/003	3/1965	*	71,386 A	3,17
294/104				
Stright	8/1978		05,238 A	4,10
Pankratz	5/1984		49,743 A	4,44
Bernier	10/1984		78,449 A	4,47
Wright B25B 7/00	10/1993	*	53,408 A	5,25
294/1			,	,
274/1.				

(Continued)

Primary Examiner — Paul T Chin (74) Attorney, Agent, or Firm — Global Intellectual Property Agency, LLC; Daniel Boudwin

(57) ABSTRACT

An elongated gripping device for grasping objects, and particularly useful for moving and adjusting logs used to build a fire. The elongated gripping device includes an elongated outer shaft having an extension shaft on an end thereof. The extension shaft includes one or more prongs on an end thereof, disposed transversely to the extension shaft. The elongated gripping device further includes an elongated inner shaft extending through the outer shaft, and having a handle at a first end thereof. The inner shaft further includes one or more prongs on the second end thereof that are arranged transversely to the inner shaft. The prongs on the inner shaft and on the extension shaft oppose one another so as to form a claw-like structure that can be used to grasp objects of various shapes and sizes by rotating the handle to actuate the prongs.

6 Claims, 2 Drawing Sheets

